



MASTER SDW-T

MASTER SDW-T 35W/825 PG12-1 1SL/12

Range of high-efficiency, discharge lamps with warm color to be used in open luminaires

Product data

General Information		Lamp Current Run-Up (Max)	
Cap-Base	PG12-1 [PG12-1]	Lamp Current (EM) (Nom)	1.0 A
Bulb Shape	T31 [T 31mm]	Ignition Peak Voltage (Max)	0.48 A
Operating Position	UNIVERSAL [Any or Universal (U)]	Ignition Supply Voltage (Min)	5000 V
Life To 5% Failures (Nom)	8000 h	Voltage (Max)	205 V
Life To 20% Failures (Nom)	12000 h	Voltage (Min)	106 V
Life To 50% Failures (Nom)	15000 h	Voltage (Nom)	86 V
Useful Life (Nom)	10000 h		96 V
ANSI Code HID	-	Controls and Dimming	
System Description	200 to 250V	Dimmable	No
Light Technical		Mechanical and Housing	
Color Code	825 [CCT of 2500K]	Bulb Finish	Clear
Luminous Flux (Rated) (Nom)	1300 lm	Bulb Material	Soft Glass
Color Designation	Golden White	Approval and Application	
Lumen Maintenance 2000 h (Nom)	95 %	Energy Efficiency Label (EEL)	B
Lumen Maintenance 5000 h (Nom)	90 %	Mercury (Hg) Content (Nom)	3.8 mg
Chromaticity Coordinate X (Nom)	479	Energy Consumption kWh/1000 h	36 kWh
Chromaticity Coordinate Y (Nom)	417	Luminaire Design Requirements	
Correlated Color Temperature (Nom)	2500 K	Bulb Temperature (Max)	350 °C
Luminous Efficacy (rated) (Nom)	40 lm/W	Cap-Base Temperature (Max)	120 °C
Color Rendering Index (Nom)	83	Operating and Electrical	
Power (Rated) (Nom)	33.0 W		


MASTER SDW-T

Product Data

Full product code	871150073402015
Order product name	MASTER SDW-T 35W/825 PG12-1 1SL/12
EAN/UPC - Product	8711500734020
Order code	928153809230
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	12
Material Nr. (12NC)	928153809230
Net Weight (Piece)	0.048 kg
ILCOS Code	STH-35-H/E-PG12

Dimensional drawing



SDW-T 35W/825 PG12-1

Product	D	O	L	C
---------	---	---	---	---

